FW048 HAZMAX S5/SRA WELLINGTON (EN 13832-3)

CONFORMITIES/STANDARDS

EN 13832-3: 2018 A,K,O,P,Q,R,T Chemical Protective Footwear
EN ISO 20345:2011 S5 SRC HRO CI FO Safety Footwear
PPE Regulation (EU) 2016/425 Personal Protective Equipment



DESCRIPTION

• HAZMAX S5/SRA WELLINGTON (EN 13832-3)
• Manufactured from proprietary Hazmax compound, providing significantly better chemical resistance than PVC or PU materials
• Chemically resistant boot certified to EN 13832-3:2018 (footwear protecting against chemicals)
• Conforms to EN 943-1 (Chemical protective clothing) and certified to this standard as part of an appropriate Respirex gas-tight suit
• Antistatic - Electrical resistance meets the requirements of EN ISO 20345:2011 A (0.1MΩ to 1,000MΩ)
• Integral 200 Joule epoxy coated steel toecap and stainless steel penetration resistant mid-sole
• Heat resistant sole EN 20345:2011 HRO, 60 seconds at 300 °C
• Cold insulation to EN ISO 20345:2011 CI
• Fuel and oil resistant upper and sole
• Vulcanized rubber sole for improved slip resistance - 30% better than a conventional safety boot sole
• Durable, cut-resistent vulcanised rubber sole, significantly extends working life, even in harsh terrain
• Cleated outsole for maximum grip in wet and oily conditions (SRC)
• Energy absorbing tunnel system in heel to EN 20345:2011 E
• Ergonomic cushioned insole (removable & machine washable) for greater wearer comfort
• Seamless construction
• Kick-off lug
• Adjustable height

SIZE AVAILABILITY

SIZE 3 - SIZE 15

FW048 HAZMAX S5/SRA WELLINGTON (EN 13832-3)

- Knitted nylon lining
- CE marked on the shaft with date and year of manufacture
- REACH Compliant
- Machine washable at up to 40°C
- Shelf life of over 10 years

Future Garments Limited
+44 121 555 1020 | info@futuregarments.co.uk | https://www.futuregarments.co.uk